



TECHNICAL DATA SHEET

Multi-purpose grease ISO-L-XCCEA2

Rebcon® Multi-purpose grease for slowly and fast running bearings.
For long-time lubrication at normal conditions. For lubricating much work equipment
e.g. in the agriculture and building industry.

Properties

- good anti-corrosive properties
- good adhesive
- resistant against oxidation
- good water resistance
- squeeze-stable

Technical Data

Colour: Light brown
Base Fluid: Mineral oil
Thickener: Lithium-12-Hydroxystearat
Consistency: NLGI 2
Dropping Point: >180°C
Basic Oil viscosity
40°C: 120 mm²/s
100°C: 11 mm²/s
Density (25°C): approx. 0.93
4-ball weld load: 2000 N
Temperature range: -30°C - +130°C
short-time: max. +150°C

Suggestions, processing and use of our products correspond to the best knowledge at printing of this leaflet and are always given without obligation. You only can serve as a clue in consideration of the changing conditions; from this no liabilities, liability and guarantee claims can be derived. Own tests must be carried out before application. Every manufacturer of our products is liable for the retention everything legal to regulations

Sitz: Hamburg; Registergericht: Hamburg; HRB 131738; Geschäftsführung: Dennis Rebling, Jan Rebling
USt-IdNr.: DE294522319; Steuernummer: 247/753/00626

Rebtec GmbH
Hein-Sass-Stieg 4
21129 Hamburg

Tel.: +49 40 22 867 41-0
Fax: +49 40 22 867 41-99
info@rebtec.de

Hypovereinsbank
IBAN: DE21200300000015642934
BIC: HYVEDEMM300

